

• In addition to routine checks for each use, PPE should regularly undergo a detailed inspection by a competent person. Petzl recommends an inspection every 12 months and after any exceptional event in the life of the product.
 • PPE inspection should be conducted with the manufacturer's Instructions for Use.
 Download the instructions at PETZL.COM.

GRIGRI BELAY DEVICES

User information

Surname

Address

Identifier

PPE information

Model

Serial number

Year of manufacture

Date of purchase

Date of first use

Manufacturer: Petzl, ZI Cidex 105A - 38920 Croles - France

				N/A
Good condition (G)	To monitor (TM)	To repair (TR)	Do not use, retire (R)	Not applicable

1. Known product history

Usage conditions or exceptional event during use (examples: fall or fall arrest, use or storage at extreme temperatures, modification outside manufacturer's facilities...):

				N/A
---	---	---	---	-----

2. Preliminary observations

- Verify the presence and legibility of the serial number and the CE mark.
- Verify that the product lifetime has not been exceeded.
- Compare with a new device to verify there are no modifications or missing elements.

3. Checking the moving side plate

- Check the condition of the moving side plate (marks, deformation, fouling, cracks, wear...). If you see a hole in the side plate, retire the product.
- On the GRIGRI +, check the condition of the wear plate.
- Check the condition of the attachment hole (marks, deformation, cracks, corrosion...).
- Check the condition of the rivets (marks, deformation, cracks, corrosion, absence of play...).

4. Checking the condition of the frame

- Check the condition of the cam and its axle (marks, deformation, fouling, cracks, corrosion...). Check the cam's mobility.
- Check the condition of the friction plate (marks, deformation, fouling, cracks...).
- Verify the absence of foreign objects (sand...) or lubricant on the rope channel.
- Check the condition of the rivets (marks, deformation, cracks, corrosion, absence of play...).

5. Checking the condition of the handle

- Check the condition of the handle (marks, deformation, cracks...).
- Check that the handle return spring is working properly.

6. Checking the condition of the selector knob (GRIGRI + only)

- Check the condition of the selector knob (marks, deformation, cracks...).
- Check the selector knob for proper function. (When rotated, the cam offers more resistance in the lead climbing position than in the top-rope position).

7. Function check

- Do a function check with the device on the harness. Do this test with your smallest diameter rope.

Comments (detail here any defects found on the product and accomplished tasks)

VERDICT	
	Product fit to remain in service
	Product unfit to remain in service

Inspected by	
Company	
Date	Next inspection date